





1:100 scale
0M 1M 2M 3M 4M 5M
1:50 scale
0M 1M 2M

PROPOSED FLOOR PLANS & ELEVATIONS 1:50@A1

1:50 scale
0M 5M 10M 15M 20M 25M 30M
1:1250 scale
0M 10M 20M 30M 40M 50M 60M



pdq consultancy
DEDICATED PROJECT DELIVERY

DRAWINGS PRODUCED IN ACCORDANCE WITH BUILDING REGULATIONS APPROVED DOCUMENTS 2023

DRAINAGE
Drains to be 100mm dia. Viva flexible jointed pipe on 100mm granular bed surrounded and covered by 300mm mineral fill (BS544). Pipe passing through sub-structure brickwork to have opening formed with concrete lintel over and covering minskew each side with rigid material. NOTE: if on site inspection drains pass through foundations, pipes are to be ducted through 200mm dia. vitrified clayware pipe with sand packing inside larger dia. pipe, with larger dia. pipes encased in 150mm thick concrete.

EXISTING FOUNDATIONS
Existing foundations to be exposed to determine adequacy for new loadings. If on site inspection foundations need remedial work, structural engineer is to be appointed by client for solution.

FOUNDATIONS
600mm wide concrete trench fill foundations at a depth to be agreed on site with local authority building control officer. If on site inspection ground conditions dictate special foundations, Structural Engineer to be appointed to design & detail foundations.

STRUCTURE & CWORK
Internal and external walls to be class B semi-engineering bricks or 100mm 7N solid concrete blocks. FL quality facing bricks to be used in external leaf from underside of DPC to two courses below finished ground level. Cavity to be filled with insitu concrete to within 225mm of lowest DPC. Opening for services/ drainage to have concrete lintel over and masked each side with rigid material.

DPC's
Horizontal DPC to external walls to be provided 150mm min. above finished ground floor level to external and internal leafs. All DPC's to be Hytoid polymer free.

GROUND FLOOR – u -value = 0.17W/m²
75mm thick condensate screed (1:3) with 25mm galvanised wire mesh reinforcement on 500 gauge polythene vapour barrier on 100mm thick Celotex GA4000 flooring insulation (or similar approved). On 100mm thick insitu concrete slab, on 1200 gauge polythene DPM, turned up at a perimeter of 100mm to be tacked & sealed to DPC, on 25mm thick sand bedding, on 150mm well compacted hardcore. Vertical upstands of insulation to be provided at perimeter of floor depth of screed p/a ratio = 0.56

EXTERNAL WALLS – u -value = 0.17W/m²
cavity wall construction 350mm o/a thickness consisting of 100mm approved facing brickwork, 150mm wide cavity filled with 150mm Knauf Dritthrm 32 insulation (or similar approved). 100mm thick loadbearing aircrete blockwork (max thermal conductivity = 0.15W/mk) internal leaf 100bs6073 parts 142, 12.5mm thick plasterboard & skim finish on plaster dabs internally. stainless steel cavity wall ties at 900mm horizontal and 450mm vertical staggered centres. doors to be closed to allow for opening. ALTERNATIVE external leaf to consist of 100mm medium density concrete blockwork finished externally with 15mm thick proprietary through coloured render.

BLOCKWORK INTERNAL LOADBEARING WALLS
100mm medium density concrete blockwork (min 7.0N/mm² & 120kg/m² min mass per unit area), finished both sides with 12.5mm thick plasterboard & skim finish on plaster dabs. All joints to be well sealed.

STUD PARTITIONS
75mm thick treated softwood framing at 600mm max centres with 12.5mm plasterboard (min density 10kg/m²) and skim finish to both sides. Partitions between bathrooms and bedroom and/or other rooms to have 25mm unfaced mineral wool batts (min density 10kg/m²) insulation between framing. Shower enclosures and partitions adjacent to baths to be finished with 12.5mm moisture resistant board.

EXISTING FIRST FLOOR?
Existing floor structure & boarding to be retained. Ground Floor Ceiling below to be removed & acoustically upgraded with ReductoClip Timber Ceiling System or similar approved. Consisting of ReductoClip resilient fixing & associated Furring Bars, to support 2no. layers of 10mm thick acoustic plasterboard with taped and staggered joints. 10mm acoustic mineral wool (60kg to be inserted between floor joists).

FIRST FLOOR
18mm tongue & grooved softwood floorboards (min mass per unit area 13kg/m²) or 19mm thick plywood under wet area floors on 47x195mm C24 grade floor joists at 450mm max centres. 12.5mm plasterboard with skim finish ceiling (min mass per unit area 10kg/m²). 100mm quilt insulation (10kg/m²) to be placed between joists.

STAIRCASE
Specialist made timber staircases to have 220mm max risers & 220mm min goings. Pitch of stairs to be a maximum 42°. Handrail to be securely fixed to height of minimum 900mm and maximum 1000mm (measured vertically above pitch line). Minimum 200mm clear headroom to be maintained throughout stair flight. Bullusters to be at 100mm max centres. Guarding to be fixed to be height of 900mm above finished floor level.

SECOND FLOOR
18mm tongue & grooved softwood floorboards (min mass per unit area 15kg/m²) or 19mm thick plywood under wet area floors on 47x195mm C24 grade floor joists at 450mm max centres. 12.5mm plasterboard with skim finish ceiling (min mass per unit area 10kg/m²). 100mm quilt insulation (10kg/m²) to be placed between joists.

WINDOWS & DOORS u -value = 1.4W/m²
Hollow profile extruded grey PVCu framed, double glazed windows (profile TS7413). All windows to be double glazed to be fitted with trickle ventilator according to background ventilation. Windows not less than 800mm total to each room. All windows to non-habitable windows to be fitted with triple ventilator providing background ventilation opening of not less than 400mm² total to each room. Opening lights to be not less than 1/20th of the rooms floor area and more than 30°, to provide rapid ventilation.

BI-FOLD DOORS u -value = 1.4W/m²
Polyester powder coated aluminium framed, double glazed bi-folding doors (by Alchemy or similar approved) incorporating flush threshold.

GLAZING – u -value = 1.4W/m²
Factory made double glazed units, to give max u -value of 1.4W/m². (as specified by window manufacturer). Glazing in the following locations to be toughened safety glass to BS6206, 1981: between f.t.i. & 800mm high. Between f.t.i. & 1500mm high in doors or side panels.

EXISTING LINTELS
All existing lintels above openings are to be exposed to ascertain their suitability for the proposed works. Structural Engineer & Building Inspector to advise.

LINTELS
Catic (or similar approved) insulated galvanised steel lintels (to BS5977) or prestressed concrete lintels or steel beams designed by structural engineer, built in with min. 150mm end bearing to each side.

FIRE PROTECTION
All exposed steel beams & lintels to be encased in 15mm thick two coat plaster OR 2no. layers of 12.5mm plasterboard with taping & staggered joints OR coated with intumescent paint by specialists to give equivalent to 1 hour fire resistance.